

Amendments to the Specification

Please amend the paragraphs of the specification identified below by paragraph numbers in the manner indicated below.

[0010] Advantageously, the at least one post is mounted on at least one ~~sprung~~ spring support member. Preferably, the at least one ~~sprung~~ spring support member biases the at least one post towards the component engaging position.

[0015] According to another aspect of the present invention, there is provided a component mounting system for mounting a component within a casing, including a component support securable to a casing; at least one post mounted on at least one ~~sprung~~ spring member, which ~~sprung~~ spring member is mounted to the support, the at least one post being operable to be engaged in at least one associated recess in the component and being movable between a component engaging position and a component non-engaging position; and a post moving device slidable relative to the at least one post and operable to move and retain the at least one post between said component engaging position and said component non-engaging position.

[0016] According to another aspect of the present invention, there is provided a computer casing including a component mounting system for mounting a component within the casing, including a component support securable to the casing; at least one post mounted on at least one ~~sprung~~ spring member, which ~~sprung~~ spring member is mounted to the support, the at least one post being operable to be engaged in at least one associated recess in the component and being movable between a component engaging position and a component non-engaging position; and a post moving device slidable relative to the at least one post and operable to move and retain the at least one post between said component engaging position and said component non-engaging position.

[0021] FIG. 4 shows a perspective view of an embodiment of post and ~~sprung~~ spring support member for the system of FIGS. 2 and 3;